



RAVENOL CVT Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211110

Oil type: Synthetic



Recommendation: BMW CVT EZL 799A, Five Hundred CFT30, Ford EU WSS-M2C-928 A, Ford Focus C-Max CFT23, Ford USA WSS-M2C933-A, Ford XT-7-QCFT Freestyle, HMMF Ultra Fluid 08260-99904, HMMF Ultra Fluid 08260-99907, Honda CVT Fluid 08200-9006, Hunan Jianglu & Rongda 150R, Hunan Jianglu & Rongda R0CF15A2, Hunan Jianglu & Rongda R0CF15A3, Hunan Jianglu & Rongda RDC15, Hunan Jianglu & Rongda RDC15-FB, Mazda TFF CVT Fluid TC JWS3320 K020-W0-051W, MB 236.20 (A 001 989 46 03), Mini Cooper CVT, Nissan CVT Fluid NS-1, Nissan KLE50 00002, Nissan KLE50 00004, Opel/GM 1940713, Punch Powertrain VT1F, Punch Powertrain VT2, Punch Powertrain VT3, Subaru CVT Lineartronic II K0425Y0711, Subaru i-CVT Fluid K0415-YA090, Suzuki S-CVT 99000-22801-000, TL 52180, Toyota CVT Fluid TC 08886-02105, VW G 052 516 A2, VW/Audi G 052 180 A1, VW/Audi G 052 180 A2, VW/Audi G 052 180 A6

Application: Passenger car

RAVENOL CVT Fluid is a synthetic ATF for the latest generation of CVT transmission.

RAVENOL CVT Fluid guarantees an optimum of power transmission.

RAVENOL CVT Fluid is based on high-quality hydrocrack oils with special additives and inhibition to ensure the proper operation of the automatic transmission.

Application Note

RAVENOL CVT Fluid was developed for use in CVT transmission (Steel Belt Continuously Variable Transmission).

RAVENOL CVT Fluid ensures a stable viscosity under high mechanical stress in the transmission elements (push belt).

Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- Neutral behaviour towards sealing materials
- Neutral behaviour by inhibition to non-ferrous metals

1L | 1211110-001

4L | 1211110-004

10L | 1211110-010

20L | 1211110-020

20L | 1211110-B20

60L | 1211110-060

60L | 1211110-D60

208L | 1211110-208

208L | 1211110-D28

1000L | 1211110-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	846,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	7,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	35,5	DIN 51562-1
Viscosity Index VI		175	DIN ISO 2909
Pourpoint	°C	-48	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

18.07.2023